



Air Handling Units



Customized configuration



Aluminum structural posts with an additional sealing fin and thermal insert



Double wall - 2" Polyurethane Sandwich Panels



Market's Best Lead Time

Reliable and leak-tight construction

Top Quality Components

Intelligent Controls Systems

MORE THAN **2,000**HOURS SALT SPRAY
TEST PROTECTION

RESISTANCE TO CORROSION



Energy recovery:

up to 92% recovery efficiency





from 800 CFM to 38 000 CFM in total capacity

Kind of unit: modular AHU's Capacity - from 800 CFM to 38 000 CFM

Energy efficiency: energy recovery system: cross-flow plate, energy wheel Placing: floor mounted unit



from 800 CFM to 4 000 CFM in total capacity

Kind of unit: modular AHU's Capacity - from 800 CFM to 4 000 CFM

Energy efficiency: energy recovery system: cross-flow plate, energy wheel Placing: floor mounted unit



from 800 CFM to 4 000 CFM in total capacity

Premium efficiency motors 2 000 h salt spray test: resistence on the external coating



TECHNICAL INFORMATION

- VFD inside the panel NEMA4
- UV Lamps Available
- Unit manufactured for the outdoor
- Rooftop Applications
 - Sectional Roof
 - Variable Intake Configurations
 Curb Ready Reals

 - · Variable Discharge Configuration
- Galvanized Steel Support
- Direct-Drive Plenum Fans with Backward Curved Polymer Composite Blades
- TEFC Motors with VFD as standard
- Single Point Power Connection
- Built in short circuit protection (circuit breakers) and main disconnect switch

CONTROLS

- Measurement and control of the constant air volume
- Constant pressure control with variable air volume
- Electric heater control
- Humidity Control
- Mixing Box Control

DESIGN

- Casing skin
- Fan Section
- Convenient
- Structural Posts









